

Model Selection

Model	Description H x W x D (in)	Airflow cfm (L/s)					Effectiveness @ 0 °C (32 °F)	Performance Highlights
		.1 (25 Pa)	.2 (50 Pa)	.3 (75 Pa)	.4 (100 Pa)	.5 (125 Pa)		
95 MAX*	Recirculating Defrost 24.5 x 18.5 x 16	76 (36)	73 (34)	70 (33)	66 (31)	60 (29)	88%	Top ported, compact unit. Ideally suited for tight installations.
100 ECM*	Recirculating Defrost 19 x 33.62 x 14.75	161 (76)	143 (68)	128 (61)	114 (54)	98 (46)	78%	Same design as 155 MAX, with a highly efficient energy-saving ECM motor.
155 MAX*	Recirculating Defrost 19 x 33.62 x 14.75	184 (87)	163 (77)	146 (69)	132 (62)	115 (54)	84%	Most popular HRV. Horizontal with door port balance. Also available in reverse model 155 MAX RX
205 MAX*	Recirculating Defrost 19 x 33.62 x 15.125	222 (105)	207 (98)	193 (91)	179 (84)	165 (78)	79%	New top port unit for flexible installations, door port balancing.
195 ECM*	Damper Defrost 19 x 49 x 14.75	191 (90)	184 (86)	177 (83)	169 (80)	159 (75)	88%	Dual core for maximum heat recovery and includes highly efficient energy-saving ECM motor.
195 DCS*	Damper Defrost 19 x 49 x 14.75	216 (101)	195 (92)	181 (85)	158 (74)	144 (68)	92%	Dual core for maximum heat recovery and energy efficiency.
300 DCS*	Damper Defrost 19 x 49 x 14.75	232 (110)	212 (100)	202 (96)	183 (86)	163 (77)	90%	Same design as 195 DCS except for greater airflows. Meets the needs of high-efficiency in larger homes.



Control Options



Lifestyle MAX
Digital Control
#99-DXPL01
(included)



or choose...

Lifestyle MAX
Programmable
Control
#99-LS01

- 5-speed operation
- 4 user operational modes
 - continuous ventilation
 - 20 min. ON, 40 min. stand-by
 - 20 min. ON, 40 min. recirculation*
 - continuous recirculation*
 - high speed override
- Built-in interface to furnace
- Automatic service reminder
- **DELUXE** fully featured 5-speed, 4 mode unit.
- Fully **PROGRAMMABLE**, allowing you to customize for your specific lifestyle.
- Dehumidstate Disable
* Not available on all models

Timers

Lifestyle 20/40/60 Minute Timer #99-DET01

- Initiates high speed operation for 20, 40 or 60 minutes

Lifestyle 20 Minute Timer #99-20M01

- Initiates high speed operation for 20 minutes



This product earned the ENERGY STAR by meeting strict energy efficiency guidelines set by Natural Resources Canada and the US EPA. This meets ENERGY STAR requirements only when used in Canada.



Visit us at www.lifebreathe.com

Model Selection

Model	Description H x W x D (inches)	Airflow cfm (L/s)					Effectiveness @ 0 °C (32 °F)	Performance Highlights
		.1 (25 Pa)	.2 (50 Pa)	.3 (75 Pa)	.4 (100 Pa)	.5 (125 Pa)		
RNC 95*	Recirculating Defrost 24.5 x 18.5 x 16	76 (36)	73 (34)	70 (33)	66 (31)	60 (29)	88%	Top ported, compact unit. Ideally suited for tight installations.
RNC5-TPD	Recirculating Defrost 18.75 x 27 x 15	169 (60)	156 (73)	149 (70)	136 (64)	126 (59)	74%	Compact unit with door port balancing, Adjustable high speed (3) settings.
RNC5-TPF	Fan Defrost 18.75 x 27 x 15	174 (82)	165 (77)	154 (73)	143 (67)	132 (62)	75%	Compact unit with door port balancing, Adjustable high speed (3) settings.
RNC 120F	Fan Defrost 18.25 x 28.75 x 9.25	152 (72)	141 (67)	131 (62)	122 (58)	114 (54)	71%	Low profile cabinet at only 9.25 inches tall. Fits in bulk and drop ceiling.
RNC 155	Recirculating Defrost 19 x 33.62 x 14.75	184 (87)	163 (77)	146 (69)	132 (62)	115 (54)	84%	Horizontal model, with door port balancing. One of our most popular units.
RNC 205	Recirculating Defrost 19 x 33.62 x 15.125	222 (105)	207 (98)	193 (91)	179 (84)	165 (78)	79%	New top port unit for flexible installations, door port balancing.
RNC 10	Damper Defrost 19 x 33.62 x 14.75	177 (83)	164 (77)	156 (73)	143 (67)	123 (58)	76%	Horizontal model with 5 ports and damper defrost. Best value for new construction.
RNC 20	Damper Defrost 19 x 33.62 x 14.75	214 (101)	206 (97)	193 (91)	184 (87)	170 (80)	67%	Same design as RNC 10. Ideally suited to larger applications.



This product earned the ENERGY STAR by meeting strict energy efficiency guidelines set by Natural Resources Canada and the US EPA. This meets ENERGY STAR requirements only when used in Canada.



Visit us at www.lifebreath.com

Control Options



Lifestyle
Dehumidistat
#99-DH01

- Initiates high speed ventilation when the indoor humidity level is above the set point.



Lifestyle RNC
Ventilation
Control
#99-BC01

- 2 Speed operation
- Standby
- Unit On/Off
- Dehumidistat



Lifestyle RNC Digital Control #99-DX01

- 4 selectable operational modes*
* Not available on all models
- 2 speed operation on each mode
- Adjustable dehumidistat function
- Dehumidistat disable
- High speed override

Timers

Lifestyle 20/40/60 Minute Timer #99-DET01

- Initiates high speed operation for 20, 40 or 60 minutes

Lifestyle 20 Minute Timer #99-20M01

- Initiates high speed operation for 20 minutes

Accessories

- Weatherhoods - 5", 6" or 7"
- Kitchen Grille - 6" x 10"
- Tech Grilles - 4", 5", 6" or 8"